



LABELLING HEAD INTREX 100+ FLEX

.....> ENTRY-LEVEL LABELLING IDEAL FOR MOST APPLICATIONS

- Maximum label width 90 mm or 160 mm
- Labelling speed up to 35 m/min
- Detachable touch control panel
- Up to 50 labelling recipes
- Multi-language control menu
- Missing label compensation
- Labelling precision 0.8 mm
- Two-position label brake
- Well-proven design
- Flex module - allows to expand the capabilities of the labelling head with additional mechanical and software functionalities



The real maximum labelling speed depends on the label, capacity, type of the labelled product and the kind of application.
The label feeding precision depends on the label and the labelled product properties.





PARAMETER

INTREX 100+ FLEX

VERSIONS	Right, Left
MAX LABEL WIDTH (HEIGHT ON THE PRODUCT)	90 mm, 160 mm
MAX LABEL ROLL OUTER DIAMETER	300 mm
LABELLING SPEED	Up to 35 m/min
LABELLING FEED PRECISION	0.8 mm
LABEL SENSOR	Optical, Ultrasonic (optional)
CONTROLLER	3" detachable touch screen
MEMORY	50 recipes
ADDITIONAL FEATURES	• Two-position label brake • Compensation of missing labels at a full speed range • Possibility to add a beacon • Ability to work with fixes or variable speed (with encoder) • Adjustment of label sensor position
DRIVE	Stepper motor
POWER SUPPLY	230 VAC, 50 Hz

The real maximum labelling speed depends on the label, capacity, type of the labelled product and the kind of application.
The label feeding precision depends on the label and the labelled product properties.

